

GAZPROMNEFT TOSOL Premix, 40, 65

GAZPROMNEFT TOSOL Premix, 40, 65 are ready-to-use traditional coolants based on ethylene glycol for internal combustion engines.

Frost protection temperature:

GAZPROMNEFT TOSOL Premix – minus 16 °C.

GAZPROMNEFT TOSOL 40 – minus 37 °C.

GAZPROMNEFT TOSOL 65 – minus 62 °C.

Application

- Cars and trucks, special equipment.

Advantages

- Excellent heat dissipation properties.
- Protection against corrosion, foaming, rubber swelling.
- The basic component of the product is ethylene glycol.
- Protection of the cooling system from freezing and boiling.

Typical physical and chemical properties

Parameters	Method	GAZPROMNEFT		
		TOSOL Premix	TOSOL 40	TOSOL 65
Appearance	Visually	Transparent homogeneous blue liquid without visible foreign inclusions		
Density at 20 °C, g/cm ³	ASTM D1122	1,046-1,051	1,073	1,092
Refractive index at 20 °C	GOST 18995.2	1,366-1,371	1,385	1,399
Boiling point, °C	ASTM D1120	103	108	159
Alkalinity reserv, ml	ASTM D1121	≥10	16,6	17,8
pH	ASTM D1287	8,0-10,5	10,1	10,2
Foamability	ASTM D1881	-	max 50 ml / 5 s	max 50 ml / 5 s
Chilling point, °C	ASTM D1177	-16	-37	-62

Specifications

GOST 28084-89, GOST 33591-2015

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

