



Gazpromneft ATF DX III Standard



Synthetic technology



Low temperature properties



Automatic transmissions

Oxidation stability



transmissions



Power steering

Gazpromneft ATF DX III Standard is a synthetic technology oil recommended for passenger cars, commercial, special and off-road machines' automatic transmissions. Due to synthetic base oil component it has high oxidation stability and prevents deposit formation. This oil has enhanced low-temperature properties and extended service life compared to mineral oils

Properties/Features/Potential benefits

- High oxidation stability → reduced deposits formation in automatic transmissions → transmission maintenance cost reduction
- Outstanding low-temperature properties → good fluidity at low temperatures providing good cold-start shifting
- Compatible with all common seal materials → excellent leakage control → oil consumption reduction

Application



- Passenger cars, commercial vehicles, special and off-road machines
- Automatic transmissions and other systems where automatic transmission fluid of GM DEXRON IIH level is specified
- Power steering systems

Specifications	Gazpromneft ATF DX III Standard
General Motors DEXRON IIIG, IIIH	\checkmark
Ford MERCON	\checkmark
Allison C-4	\checkmark
Caterpillar TO-2	\checkmark

Typical characteristics

Properties	Method	Gazpromneft ATF DX III Standard
Kinematic Viscosity, mm²/s: at 40 °C at 100 °C	ASTM D 445	37,5 7,3
Viscosity Index	ASTM D 2270	164
Brookfield at -40 °C, mPa*s	ASTM D 2983	16500
Flash Point (COC), °C	ASTM D 92	232
Pour Point, °C	ASTM D 97	-46
Density at 20 °C, kg/m ³	ASTM D 4052	852

Health, Safety, Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Certified

ISO 9001

ISO 14001



ISO 45001



While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: Technical.com (Source (Source (Source)) and (Source) and (So