



Gazpromneft Moto 2T

Two-Stroke Engine Oil



Engine oil





Engine cleanliness



Small 2T gasoline engines



Low ash formulation



Excellent friction performance

Gazpromneft Moto 2T is high quality two-stroke engine oil that has been developed for small to medium size aircooled two-stroke engines. Gazpromneft Moto 2T is formulated with modern low ash additive system which offers protection against scuffing of piston rings and liner wear by minimizing piston ring deposits. Mixing with the fuel should be in accordance with the manufacturer's recommendations.

Applications



• Land based air-cooled two-stroke engines

- Two-stroke engines where JASO FB oils are recommended
- Motorcycles, go-karts, snowmobiles
- Lean oil/fuel ratio chain saws, lawnmowers and other gardening equipment

Features	Advantages and Potential Benefits	
Cleaner combustion and reduced deposits		
in combustion area	ignition and extend spark plug and valve life	
Reduced Smoke	Less smoke to improve environmental concerns and riding comfort	
High temperature deposits control	Cleaner engines resulting in reduced ring sticking and cylinder	
	scuffing, and extended engine life	
Wear protection	Good film strength under a full range of engine operating conditions	
	protecting against cylinder scuffing and bearing wear resulting in	
	increased engine life	

Meet the requirements

- ISO-L-EGB
- JASO FB

Typical Characteristics

Properties	Method	Gazpromneft Moto 2T
Color	visually	red
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	8,4
Viscosity Index	ASTM D2270	93
Flash Point (COC), °C	ASTM D92	220
Pour Point, °C	ASTM D97	-20
Density @15°C, kg/m ³	ASTM D4052	884
Sulfated Ash, wt%	ASTM D874	0,06

ISO 9001

ISO 14001

SO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>OilSupport@gazprom-neft.ru</u> 04/2020

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

ISO 9001

ISO 14001

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com

V ISO/TS 16949

OHSAS 18001

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>OilSupport@gazprom-neft.ru</u> 04/2020