



# Gazpromneft ATF DX III

Automatic Transmission Fluid



Automatic Transmission Fluid



Semisynthetic



Power steering systems



Optimal friction performance



High wear protection



Oxidation stability

**Gazpromneft ATF DX III** is high quality automatic transmission fluid recommended for most passenger car and commercial automatic transmissions. It is designed to maximize transmission performance, reduce transmission wear, prevent leaks and maintain smooth shifting. Gazpromneft ATF DX III can be used in power steering systems and hydraulic applications where automatic transmission fluid is specified.

# Applications



- Passenger and commercial automatic transmissions
- · Power steering systems and hydraulic applications where automatic transmission fluid is specified

Features	Advantages and Potential Benefits	
Excellent thermal and oxidation stability	Reduced deposits and sludge build-up help provide outstanding	
	transmission performance even under severe driving conditions	
Good low temperature performance	Good fluidity at low temperatures providing good cold-start shifting	
Good friction properties	Improved transmission efficiency and smooth shifting performance	
Compatible with all common seal	Excellent leakage control	
materials		

# Meet the requirements

- General Motors DEXRON IIIH
- General Motors TASA
- MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.11
- Allison C-4
- BMW LA 2634, LT 71141
- Caterpillar TO-2
- Ford MERCON
- MAN 339 Type V1/Z1
- Voith H55.6335
- Volvo CE 97340
- ZF TE-ML 02F, 05L, 09, 11B, 21L

## **Approvals**

- ZF TE-ML 03D, 04D, 14A, 17C
- Volvo 97341

# ISO 9001

www.gazpromneft-oil.com

**ISO 14001** 

GAZPROMNEFT – LUBRICANTS, LTD. WI 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia ma Fel: +7 (495) 642-99-69 da Fax:+7 (495) 921-48-63 rec ISO/TS 16949 ISO 45001

01

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <u>Techservice@gazprom-neft.ru</u> 03/2022

#### **Typical Characteristics**

Properties	Method	Gazpromneft ATF DX III
Color	visually	red
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	7,6
Brookfield @-40°C, mPa·s	ASTM D2983	18000
Flash Point (COC), °C	ASTM D92	217
Pour Point, °C	ASTM D97	-50
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	860

#### Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

## ISO 9001

#### **ISO 14001**

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com ISO/TS 16949

ISO 45001

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: <a href="mailto:Techservice@gazprom-neft.ru">Techservice@gazprom-neft.ru</a> 03/2022