



# Gazpromneft Moto 4T 20W-50

Four-Stroke Motorcycle Engine Oil



Engine oil





Engine cleanliness



Small 4T engines



Wear protection



Excellent friction performance

**Gazpromneft Moto 4T 20W-50** is high quality mineral oil designed for general use in many types of motorcycles and four-stroke engines. It formulated with highly refined mineral oils and thoroughly selected additives to provide good engine cleanliness, protection against wear and corrosion.Gazpromneft Moto 4T 20W-50 is perfect choice for hot climate operation.

# Applications



- · Four-stroke motorcycle engines where API SG or JASO MA2 fluids are required
- Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump)
- Small four-stroke gasoline engines requiring API SG performance (or lower)
- Gardening equipment that specify 20W-50 viscosity grade
- Four stroke outboard/inboard water/air-cooled engines

Features	Advantages and Potential Benefits	
Wet clutch compatible	Optimal frictional characteristics for maximum power transfer, smooth	
	shifting and proper protection of the wet clutch	
Wear protection	Protection throughout the range of operating conditions to extend	
	engine life	
Thermal and oxidation stability	Resists oil thickening during whole drain interval	
Detergent and dispersant properties	Control deposits formation to prevent sludge and keep engine cleaner	
Good corrosion protection	Protects critical engine components	

## Meet the requirements:

API SG

JASO MA2

## ISO 9001

www.gazpromneft-oil.com

ISO 14001

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63

#### ISO/TS 16949

ISO 45001

CERTIFIED

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: Techservice@gazprom-neft.ru11/2021

## **Typical Characteristics**

Properties	Method	Gazpromneft Moto 4T 20W-50
SAE Viscosity Grade	SAE J300	20W-50
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	170,4
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	18,4
Viscosity Index	ASTM D2270	120
Flash Point (COC), °C	ASTM D92	242
Pour Point, °C	ASTM D97	-31
Density @20°C, kg/m <sup>3</sup>	ASTM D4052	888
Total Base Number, mg KOH/g	ASTM D2896	7,3

## Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

### ISO 9001

#### **ISO 14001**

GAZPROMNEFT – LUBRICANTS, LTD. 14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia Tel: +7 (495) 642-99-69 Fax:+7 (495) 921-48-63 www.gazpromneft-oil.com

#### ISO/TS 16949

ISO 45001

**CERTIFIED** 

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: Techservice@gazprom-neft.ru 11/2021